

# ROTOR-RAKE

## BLEC ROTOR-RAKE



- Large diameter rotor for heavy working
- Optional spring tine or long tine rotors
- Duplex chain drive with overload clutch
- Special wide angle pto shaft drive
- Optional laser guided depth control

The BLEC Rotor Rake is available with either the multi-tine fine tooth rotor for raking stones off down to 20mm size or the alternative bolt on long tine for deeper raking down to 10cm and removing stones from 25mm and larger. The rake is fitted with a hydraulic bi-angling rotor with duplex chain drive, overload clutch and heavy duty gearboxes. The working principle is simple but effective – a contra rotating rotor fitted with high grade teeth positioned in a spiral sequence forking out unwanted stones and debris to the front and by angling the rotor all debris is moved to the side, leaving a clean raked finish. The Rotor Rake is popular for ‘cleaning’ during the



Model		3000
Model Number		152.300.002
Tractor hp required (min-max)		65-100 with double acting valve needed
Working width cm		300 cm
Rotor system		Fixed solid tines
Bi Angling		Hydraulic
Max work output per hour		12,000 m <sup>2</sup>
Max working depth mm		50mm
Raked stone size down to mm		20mm
Weight kg		1200kg
Dimensions WxLxH cm		320 x 205 x 130
Options		
Laser guided preparation kit		252.300.004
Spring Tine Rotor		252.300.000